

- ~ Perfect match between drive station and energy consumption of grinding, energy saving to the fullest extent possible.
- ~ Forming a closed system with classifier, with negative pressure transport, without powder pollution.

应用范围(Application):

- ~ XJ MNYXZ [/ MC [/ [\ [/] ^ [/ [_ / % ` a `
- ~ b J MNY [c / - [/ d , e / f g h / i j [/ " # k l / m c n a `
- ~ Soft material: calcite, marble, limestone, barite, gypsum, slag etc.
- ~ Hard material: quartz, felspa, carbonundum, corundum, fine cement etc.

技术参数(Technical Parameter):

• s Item	D * + #				
1250s' [K(())	0.8	1	1.5	2	3
	1500	2200	3300	4000	7500
	1400	1900	2900	3500	6500
	1000	1400	2200	2700	4400
	450	580	880	1100	1760
	§ 1.5X5	§ 1.83X4.5	§ 1.83X6	§ 2.2X4	§ 2.2X6 , § 2.4X6 § 2.6X6
	110	160	220	250	560
	HFW500 or HFW3315	HFW4315	HFW4400 or HFW6315 or 2HFW3315	HFW3500	HFW4500 or HFW6400 or 2H
	% 300	% 380	% 550	or2HFW4315	% 1130
, - .) L ! Fliter area' m²#	120	160	250	% 700	500
B- &O Thickness of dust					

~ Y1 / > o p q r > t ! 1250 s] t u v (All of the parameters above are according to 1250 mesh GCC) `

2 / w T A P & N 9 x y z = > o p q { | p } (As different material from different places, the parameter is just for your reference) `